



CABLE DUCT DETAIL
CUSTOMER TO SUPPLY COVER, 5mm THK, X 184mm WIDE
INSTALLED AFTER FINAL FIELD WIRING & PIPING

Approximate Machine Weight
1250-510 Saw - 5037 kg

SAW COOLANT RECOMMENDATION:
USE PEDDINGHAUS "PEDDI COOL" VEGETABLE BASE COOLANT
THIS PRODUCT IS FOR MIST COOLANT SYSTEMS
DO NOT MIX THIS COOLANT WITH WATER

CUSTOMER NOTE!!!!
*This Saw Is Manufactured
At A 630mm Passive Height
Require A CUSTOMER SUPPLIED
Pit Or Platform To Achieve Any
Other Passive Height Requested.*

1250 BAND SAW NOTES:

- 1.) Passline of Equipment Based on 630mm from Floorline
- 2.) Concrete Under Equipment/Beams & Pits to be a Minimum of 200mm Thick
- 3.) Primary 380 V., 3 Ph., 50 Hz. [Req'd @ each]
- 4.) Total kw for Equipment = 15 kw 49 Amps
- 5.) Air Requirement: 6 bar, .057 SCMM Min. Free Air [Req'd @ Saw]
- 6.) Hydraulic Oil (Mobil DTE #24 Or Equal) [Req'd @ Each] [1113 L. Total]
- 7.) Anchor Bolts For 1250 Saw: 12mm ITW Red Head WS-1270 Or Equal [8 Req'd]
- 8.) Anchor Bolts For Safety Stands 20mm ITW Red Head WS-3470 or Equal [16 Req'd]
- 9.) Saw Coolant: Peddi Cool } Gal. Req'd }

E					
D					
C					
B					
A					
REV	REVISION/CH.#	BY	DATE	THIS DRAWING IS THE PROPERTY OF PEDDINGHAUS CORP. AND IS NOT TO BE USED IN ANY MANNER DISSEMINATE, TO THE EXTENT OF SAID COMPANY	
				Peddinghaus Corp. BRIDGEV. ILL. U.S.A. 1250-510 Band Saw For	
				UNPARENT Safety Model Because of the difficulty to effectively guard the responsibility to prevent access by unauthorized personnel and to provide safe craning. DRAWN BY: SCALE: 1:30 DATE: CHECKED BY: DATE: DWG. NO.	